



MATERIAL SAFETY DATA SHEET

Version 1.1
Issued 21 January 2008

I. PRODUCTION IDENTIFICATION

Product name: High Carbon Steel Shot, High Carbon Steel Grit, Sigma Steel Abrasives
Manufacturer: WINOA – (North America, Europe, South Africa)
Web Site: www.Abrasivesllc.com
Address: 1 Abrasives Ave, Bedford VA, USA
24 Field Road, Lilianton, Boksburg, South Africa
Telephone: +27 11 823 4443
Fax: +27 11 823 3555

Product Description: Steel Shot and grit comprise steel particles of size range 0.025mm up to 4mm diameter.

Chemical Family: Ferrous

II. Hazardous Ingredients.

The term HAZARDOUS should be interpreted as a term required and defined by laws, regulations, Statutes or ordinances, and does not necessarily imply the existence of any hazard when the products are used as directed by Beta Steel steel.

<u>Chemical Name</u>	<u>CAS Reg. No</u>	<u>% Weight</u>	<u>ACGIH TLV (mg/m³)</u>	<u>OSHA PEL(mg/m³)</u>
Carbon (C)	7740-44-0	<1.20	3.5 (Carbon Black)	3.5 (Carbon Black)
Iron (Fe)	7439-89-6	Balance	5 (As Oxide Fume)	10 (Total Particulate)
Manganese (Mn) Elemental and Inorganic compounds, as Mn Fume as Mn and Mn Oxide	7439-96-5	<2.0	0.2 (Fume)	5 (Ceiling) 5 (ceiling)
Silicon (Si) As Silicon Dioxide (SiO ₂)	7440-21-3 14808-60-7	<4.0 0.00	10 (Dust). 0.05 (Respirable fraction)	5 (Respirable) 10/(%SiO ₂ +2); SiO ₂ measured as Respirable fraction

III. PHYSICAL DATA


Cast steel shot and grit is in a non-hazardous condition when received. Fine metallic dust is generated as the shot breaks down from impact and wear during normal use. The Fe content of the product is greater than 90% and thus the dust or fume produced will consist of mainly of Iron Oxide, this dust so created can be a small explosion hazard.

Boiling Point:	3123-3423°C	Melting Point:	1410°C - 1480°C
Specific Gravity (at 293°K):	7.7g.ccm	Vapour Pressure	Not Applicable
% Volatile by volume	Not Applicable	pH:	Not Applicable
Evaporation Rate	Not Applicable	Vapour Density	Not Applicable
Solubility in Water	Not Applicable	Percent Solid by Weight	100%



IV. FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable
Auto-ignition Temperature: (Solid iron exposed to oxygen)-1200°K
Flammability Limits: Not Applicable
Cast steel shot and grit will not burn or explode. A mild fire or explosion hazard situation may be created due to the fine dust that may result from use, when the vacuum condition of the shot blaster is poor. Fire extinguishing method for dust created due to use-use Class D extinguishing agents or dry sand to exclude air. Do not use water or other liquids or foam.



NFPA HAZARD RATING

4= Extreme	3=High	2=Moderate	1=Slight	0=Insignificant
Health (blue): 0	Flammability (red): 0	Reactivity (yellow): 0	Special (Colourless):	

V. HEALTH HAZARD DATA

Threshold Limit Values: Permissible exposure limits – see Section II

Carcinogenicity:

Fumes can be generated by welding or flame cutting surface containing new or used stainless steel shot or the dust created by use of the abrasive. Welding or flame cutting may convert a small portion of the chromium to hexavalent chromium [VI]. IARC reports that welding fumes are possibly carcinogenic to humans.

Over exposure to dust and fumes may cause mouth, eye and nose irritation. Prolonged over exposure to manganese dust or fume affects the central nervous system. Chronic over exposure can cause manganese poisoning and attendant apathy, loss of appetite, uncontrolled laughter, insomnia followed by sleepiness, headache, difficulty in walking, frequent falling, tremors, salivation sweating and mental detachment. Prolonged over exposure to iron oxide fume can cause siderosis or “iron pigmentation” of the lung. It can be seen on a chest x-ray but causes little or no disability.

Target Organs: Lung for chromium and lung and nasal for nickel

Primary Routes of Entry: Inhalation of dust formed during use or shot or dust particles in eyes



Emergency and First**Aid Procedure:**

If inhaled, move out of the area into fresh air. Flush eyes with running water and have any remaining particles removed from eyes by a qualified person.

VI. REACTIVITY DATA**Stability:**

Stable

Hazardous polymerization:

Will not occur

Hazardous decomposition products:

None, Shot will break down into progressively smaller particles and dust during normal use.

VII. SPILL OR LEAK PROCEDURES

Shot spilled or leaked onto floors can create hazardous walking conditions. No special precautions need to be followed when cleaning up spills or leaks of shot. When cleaning up large quantities of dust an OSH approved respirator should be used. Spilled shot can be reclaimed for reuse or disposed of as a non-hazardous solid waste. Collected dust from blast cleaning or shot preening operations always contains contaminants from the surface of the parts being processed and therefore the dust may be classed as hazardous waste and, as such, must be disposed of according to appropriate local, state or federal regulations.

VIII. SPECIAL PROTECTION INFORMATION**Ventilation:**

General Ventilation and local exhaust should be provided to keep the dust levels below the TLV's shown in Section II

Respiratory protection:

If the dust created by use exceeds the ACGIH TLV's and OSHA PEL's indicated in Section II, an OSH approved respirator should be worn.

Eye Protection:

Approved safety glasses with eye shields should be worn

Other Protective**Equipment:**

None required

IX. SPECIAL PRECAUTIONS**Precautions to be taken**

in handling and storage: Observe maximum floor loading limitations

The above information is believed to be accurate based on the most current data available. Abrasives MFG LLC makes no warranty, either expressed or implied, with respect to such information, and assumes no liability resulting from its use. Abrasives-MFG LLC shall not be liable for any claims, losses, or damages of any Third party or for lost profits or incidental or consequential damages, howsoever arising.

The conditions or methods of handling, storage, use and disposal of the product are beyond Abrasives-MFG LLC's control and may be beyond our knowledge. For this and other reasons, Abrasives-MFG LLC does not assume any responsibility and expressly disclaims liability for loss, damage or expense arising out of, or in any way connected with, the handling, storage, use or disposal of the product.



.